

LED PRO

Simple & Flexible Solution

LED FLEXIBLE LINEAR LIGHT

PRODUCT INFORMATION

- Excellently waterproof and anti-dust LED strips with professional design to guarantee lighting performance.
- It not only ensure high quality of lighting color consistency but also protect products outdoor against from harsh environments outdoors.
- ILLUS LED FLEXIBLE LINEAR Light gives the customer the flexibility to choose between 7 CCT based on their specific need with lumen package from 640 lm to 940 lm.

BENEFITS

- Water proof and vivid light color.
- Less maintenance cost and less concerns on water invasion.

FEATURES

- High CRI>92.
- Operating voltage DC24V.



**BEYOND LIGHT..
TO THE LAST DETAILS!**

AREAS OF APPLICATION



Hospitality



Shopping Center



Commercial



Educational Center


TECHNICAL OPERATING & ELECTRICAL DATA

IP Rating	IP67 (silicon extrusion <hollow version>with 3M tape at back)
Power	10W
LED Quantity	126pcs/meter
Lumen	from 640-940lm/M+/-10%
PCB	Double PCB whole thickness 0.25mm, white color, 10mm, copper thickness 25um x 3pcs (3OZ)
Chip Size	2.8x3.5x0.8mm
L70	>20000H
Input	DC24V
Maximum Length	5M/Reel
Cutting Unit	Each 7 led is cuttable (cutting space 5.5cm)
Packing	Male & female DC connector, 5m/reel into a anti-static bag, 20 bags into a master carton

SPECIFICATIONS

Code No.	Model No.	Lumen	CRI	CCT
611866	ILS10LVST918WW02	640lm	95	1800K
611867	ILS10LVST922WW02	800lm	95	2200K
611868	ILS10LVST927WW02	860lm	95	2700K
611869	ILS10LVST930WW02	900lm	95	3000K
611870	ILS10LVST935WW02	910lm	95	3500K
611871	ILS10LVST940NW02	920lm	95	4000K
611872	ILS10LVST950DL02	940lm	95	5000K

DIMENSIONS



611866 - 611867 - 611868 - 611869 - 611870 - 611871 - 611872

ACCESSORIES

LED FLEXIBLE LINEAR LIGHT CONNECTOR
AVAILABLE AS AN ACCESSORY

Code No.	Model No.	Power	Input	Output	Frequency	Dimensions
612307	ILSLVST1HFC03					
612311	ILSLVST2HFC05					
612308	ILSLVST2HFC06					
611944	ILSLVRDIMMCD01	144W	DC24V	DC24V	433.92Hz	40x85x6mm
611948	ILS75W24VCG01	75W	AC220-240V	DC24V	50/60Hz	78x110x36mm
611949	ILS100W24VCG01	100W	AC220-240V	DC24V	50/60Hz	98x130x41mm
611950	ILS150W24VCG01	150W	AC220-240V	DC24V	50/60Hz	98x160x50mm

APPLICATION PICTURE



This image is for display purpose only, the image may differ from the actual product, as the product is subject to modification provided without prior notice.

LED FLEXIBLE LINEAR LIGHT

**BEYOND LIGHT..
TO THE LAST DETAILS!**



Carrer de la Vall de la Ballestera, 64, 46015 València, Valencia, España, Tel: +34619824456

www.illusillumination.com

illus illumination reserve the right to make dimensional, design and technical alternations without prior notice. illus illumination endeavor to ensure that any advice, recommendation or information it provides in product literature is accurate and correct. However due to the fact that illus do not have direct control on where and how the products are installed, illus illumination cannot accept any liability either direct or indirect arising from the use of illus products whether or not in accordance with any advice, specification, recommendation or information provided by illus illumination or its distributors.