

Make your boundaries Stand Out

LED RECESSED WALL LUMINAIRE SERIES

PRODUCT INFORMATION

- Surface mounted, exterior-rated and compact sized architectural LED edge lighting luminaire that is designed for façade and outdoor decorative lighting applications.
- Ideal for edges lighting on windows and doors inner frames, building façades, landmarks and monuments.
- ILLUS LED RECESSED WALL Luminaire gives the customer the flexibility to choose between 2 models based on their specific need.

BENEFITS

- Unique optical distribution to highlight the inner frames or outer edges of windows, balconies or doors.
- Compact size.
- Light weight.

FEATURES

- High CRI>80.
- Operating voltage AC 220-240V.
- Non dimmable.



AREAS OF APPLICATION





Hospitality

Shopping Center





Commercial

Educational Center




I TECHNICAL OPERATING & ELECTRICAL DATA

Body Material	Die Casting Aluminum with ABS
IP Rating	IP65
CRI	80
Voltage	AC220-240V
Frequency	50/60Hz
Dimming	Non- Dimmable
Mounting Type	Recessed on Wall
Lamp Type	Indirect
Life Span	50000h

SPECIFICATIONS

Code No.	Model No.	Power	Lumen	Efficacy	CCT	Body Color
612297	ILS3.5RMOWL01	3.5W	6	1.71	3000K	black+white
612298	ILS3.5RMOWL02	3.5W	16	4.57	3000K	black

DIMENSIONS



APPLICATION PICTURE



LED RECESSED WALL LUMINAIRE SERIES

BEYOND LIGHT..
TO THE LAST DETAILS!

