

DIVERTRON 60Hz

SUBMERSIBLE MULTI-IMPELLER ELECTRONIC PUMPS





TECHNICAL DATA

Flow rate: from 1 m³/h (4,4 GPM) to 6 m³/h (26,4 GPM)

Head up to: 45 m (148 ft) - 900 version
30 m (98 ft) - 650 version

maximum operation depth: 12 m (39 ft)

Type of pumped liquid: clean, free from solid or abrasive substances, non-viscous, non-aggressive, non-crystallized and chemically neutral

Liquid temperature range: from 0°C (32 F) to +40°C (104 F)

Maximum immersion depth: 15 (49 ft)

Flanges, thread: 1" (supplied as standard with a four-section fitting-reducer)

Pump maximum diameter: 160 mm (6.3 in)

Impeller/s material: technopolymer

Maximum number of starts: 20/h

Protection class: IP 68

Motor insulation class: F

Single phase power input: 115 or 230 V 60 Hz

Power cable (m) and plug: 15 m (49 ft) with power plug

Possible type of installation: fixed or movable in vertical position

Special versions on request: cable of different length, different type of power plug

Multi-impeller submersible pump with integrated electronic for automatic switching on and off. There are versions with two or three impellers available. The pump is designed for pressurization, gardening and irrigation in residential building service.

CONSTRUCTION FEATURES OF THE PUMP

Pump body and impellers in technopolymer to resist corrosion and oxidation. The delivery has an integrated non-return valve. There are version with anti-debris filter in technopolymer or fitting with brass insert for use with float suction kit (the X version). Version with float switch also available.

CONSTRUCTION FEATURES OF THE MOTOR


Asynchronous motor. Motor shaft in stainless steel AISI 416 + AISI 304. Integrated starting capacitor and thermal protection against overheating of the motor.

FEATURES OF THE ELECTRONIC

The electronics allow automatic switching on and off. The pressure switch and the flow sensor are integrated. Dry running protection. Quick access to the capacitor compartment.

MATERIALS

N°	PARTS		MATERIALS
1	BASE		TECHNOPOLYMER
2	INSPECTION CAP		EPDM
3	NUT		SS A2
4	WASHER		SS A2
5	FIRST STAGE CASE		TECHNOPOLYMER
6	FRONT FLOATING RING		TECHNOPOLYMER
7	DIFFUSER		TECHNOPOLYMER
8	BACK FLOATING RING		TECHNOPOLYMER
9	STAGE CASE		TECHNOPOLYMER
10	IMPELLER		TECHNOPOLYMER/SS AISI 304
11	SHAFT		SS AISI 303
12	FINAL DIFFUSER CAP		TECHNOPOLYMER
13	MOTOR FLANGE		TECHNOPOLYMER
14	MECHANICAL SEAL		CARBON-IMPREGNATED RESIN/CERAMIC/NBR
15	OR GASKET		EPDM
16	OR GASKET		EPDM
17	MOTOR	CAP	SS AISI 304
		MOTOR SHAFT	SS AISI 416
18	BODY		TECHNOPOLYMER
19	OR GASKET		EPDM
20	COVER		TECHNOPOLYMER
21	NON-RETURN VALVE		TECHNOPOLYMER/NBR/AISI 302/AISI A2/FERRITE
22	PRESSURE SWITCH		TECHNOPOLYMER/SILICONE
23	SAND FILTER		TECHNOPOLYMER
24	OR GASKET		EPDM
25	OUTLET COVER		TECHNOPOLYMER
26	INSERT		BRASS
27	CAPACITOR COMPARTMENT COVER		TECHNOPOLYMER
28	CABLE FLANGE		TECHNOPOLYMER
29	HANDLE		TECHNOPOLYMER





PERFORMANCE AT 60 HZ

MODEL	HYDRAULIC DATA								
	Q=m³/h	0	1,2	1,8	2,4	3,0	3,6	4,2	4,8
	Q=l/min	0	20	30	40	50	60	70	80
	Q=gpm	0	5.3	7.9	10.6	13.2	15.9	18.5	21.1
DIVERTRON 900 230 V	H (mt / ft)	45,2/148.3	42,1/138.1	39,7/130.3	36,7/120.4	33,7/110.6	29,5/96.8	24,9/81.7	19,5/64.0
DIVERTRON 900 115 V		45,8/150.3	42,9/140.8	40,5/132.9	37,3/122.4	34,2/112.2	30/98.4	25,5/83.7	20/65.6
DIVERTRON 650 230 V		29,7/97.4	27,1/88.9	25,2/82.7	23/75.5	20,9/68.6	18/59.1	14,9/48.9	10,8/35.4
DIVERTRON 650 115 V		29,9/98.1	27,9/91.5	26,1/85.6	24,1/79.1	22,1/72.5	19,4/63.7	16,1/52.8	12,5/41.0

ELECTRICAL DATA AND DIMENSIONS

MODEL	ELECTRICAL DATA							DIMENSIONS							Q.TY X PALLET	WEIGHT (kg / lb)	
	POWER INPUT 60 Hz	P1 W	P2 NOMINAL		In A	CAPACITOR		A (Ø)	H (mm / in)	H1 (mm / in)	H2 (mm / in)	H3 (mm / in)	PACKING DIMENSIONS				
			kW	HP		µF	V						L/A (mm / in)	L/B (mm / in)	H (mm / in)		
DIVERTRON 900	230 V	910	0.61	0.8	4	12.5	450	160	536 / 21.1	517 / 22.5	503 / 19.8	596 / 23.5	550 / 21.65	195 / 7.68	250 / 9.84	32	11 / 24.25
DIVERTRON 650	230 V	630	0.38	0.5	2.8	7	450	160	488 / 19.2	469 / 18.5	455 / 17.9	548 / 21.6	550 / 21.65	195 / 7.68	250 / 9.84	32	9.5 / 20.94
DIVERTRON 900	115 V	1000	0.62	0.83	9.2	35	250	160	536 / 21.1	517 / 22.5	503 / 19.8	596 / 23.5	550 / 21.65	195 / 7.68	250 / 9.84	32	11 / 24.25
DIVERTRON 650	115 V	650	0.45	0.6	6	30	250	160	488 / 19.2	469 / 18.5	455 / 17.9	548 / 21.6	550 / 21.65	195 / 7.68	250 / 9.84	32	9.5 / 20.94



The performance curves are based on kinematic viscosity values = 1 mm²/s and density equivalent to 1000 kg/m³. Curve tolerance according to ISO 9906.

NOTES

DNA

P U M P S S E L E C T O R

On-line selection tool



DAB PUMPS LTD.
6 Gilberd Court
Newcomen Way
Severalls Business Park
Colchester
Essex
CO4 9WN - UK
salesuk@dwgroup.com
Tel. +44 0333 777 5010



DAB PUMPS IBERICA S.L.
Calle Verano 18-20-22
28850 - Torrejón de Ardoz - Madrid
Spain
Info.spain@dwgroup.com
Tel. +34 91 6569545
Fax: +34 91 6569676



DAB PUMPS (QINGDAO) CO. LTD.
No.40 Kaituo Road, Qingdao Economic
& Technological
Development Zone
Qingdao City, Shandong Province - China
PC: 266500
sales.cn@dwgroup.com
Tel. +86 400 186 8280
Fax +86 53286812210



DAB PUMPS BV
'tHofveld 6 C1
1702 Groot Bijgaarden - Belgium
info.belgium@dwgroup.com
Tel. +32 2 4668353



DAB PUMPS HUNGARY KFT.
H-8800
Nagykanizsa, Buda Ernő u.5
Hungary
Tel. +36 93501700



DAB PUMPS DE MÉXICO, S.A. DE C.V.
Av Amsterdam 101 Local 4
Col. Hipódromo Condesa,
Del. Cuauhtémoc CP 06170
Ciudad de México
Tel. +52 55 6719 0493



DAB PUMPS POLAND Sp. z o.o.
Ul. Janka Muzykanta 60
02188 Warszawa - Poland
polska@dabpumps.com.pl



DAB PUMPS B.V.
Albert Einsteinweg, 4
5151 DL Drunen - Nederland
info.netherlands@dwgroup.com
Tel. +31 416 387280
Fax +31 416 387299



DAB PUMPS INC.
3226 Benchmark Drive
Ladson, SC 29456 - USA
info.usa@dwgroup.com
Tel. 1- 843-797-5002
Fax 1-843-797-3366



DAB PUMPS OCEANIA PTY LTD
426 South Gippsland Highway,
Dandenong South VIC 3175 - Australia
info.oceania@dwgroup.com
Tel. +61 1300 378 677



DAB PUMPS GMBH
Am Nordpark 3
D - 41069 Mönchengladbach - Germany
info.germany@dwgroup.com
Tel. +49 2161 47388-0
Fax +49 2161 47388-36



DAB PUMPS SOUTH AFRICA (PTY) LTD
Twenty One Industrial Estate,
16 Purlin Street, Unit B, Warehouse 4
Olifantsfontein -1667 - South Africa
info.sa@dwgroup.com
Tel. +27 12 361 3997



PT DAB PUMPS INDONESIA
Satrio Tower lantai 26
unit C-D, Jl. Prof. Dr. Satrio Kav. C4,
Kel. Kuningan Timur, Kec. Setiabudi, Kota Adm.
Jakarta Selatan, Prov. DKI Jakarta. - Indonesia
Tel. +62 2129222850