

TECHNICAL DATA

Sb017-2S-12H

Stainless Steel profile for floor and wall.

reference number : SB017

Size: 12X8X2440 mm
12X20X2440 mm

Thickness: 0.8 mm

CH01370001	Sb017-1S-12H Silver Shiny 8 X 2440	Silver Shiny
CH01370002	Sb017-2S-12H Gold Shiny 8 X 2440	Gold Shiny
CH01370003	Sb017-3S-12H Rose Gold Shiny 8 X 2440	Rose Gold Shiny
CH01370004	Sb017-4S-12H Black Shiny 8 X 2440	Black Shiny
CH01370005	Sb017-1B-12H Silver Brushed 8 X 2440	Silver Brushed
CH01370006	Sb017-2B-12H Gold Brushed 8 X 2440	Gold Brushed
CH01370007	Sb017-3B-12H Rose Gold Brushed	Rose Gold Brushed
CH01370008	Sb017-4B-12H Black Brushed 0.8 X 2440	Black Brushed
CH01370009	Sb017-1S-12H Silver Shiny 20 X 2440	Silver Shiny
CH01370010	Sb017-2S-12H Gold Shiny 20 X 2440	Gold Shiny

description	Standard
Length	2440 mm
Width	8 - 20 mm
Thickness	0.8 mm
Depth	12 mm
Material	Stainless Steel
Type	304
Fire resistance:	MO (UNE 23-727-90)
Appearance and color	EN 12373-1
Corrosion resistance	High corrosion resistance
Operability	High in various places
Rust resistance	Stainless
Magnet	Not magnet attraction
Heat and cold resistance	High

Installation :

It's widely applied to transition of tile, stone, wooden laminates, door boards and wall decorative strips.

- 1.Cut profile to the desired length and apply the adhesive on the support where the profile will be laid.
- 2.Remove carefully any remains of oil, fat and dirt from the surface where the profile will be laid.
- 3.Apply the adhesive to the surface of the substrate.
- 4.Insert the profile into the gap between the tile (wood board, door or stone, etc.).
- 5.Remove immediately all the remains of grout from the surface of the profile and tile (wood board, door or stone, etc.).

Cleaning and maintenance :

We recommend: Wash the surface with soapy water or a mild detergent. Always rinse with clean water. Dry with a soft cloth.

Checked By QUALITY DEPARTMENT