

TECHNICAL DATA

Sb018-1S-12H
Stainless Steel profile for floor spacer

reference number : SB018

Size: 12X3X2440 mm
12X3X2500 mm

Thickness: 0.8 mm

CH01370014	Sb018-1S-12H Silver Shiny 3 X 2440	Silver Shiny
CH01370015	Sb018-2S-12H Gold Shiny 3 X 2440	Gold Shiny
CH01370016	Sb018-3S-12H Rose Gold Shiny 3 X 2440	Rose Gold Shiny
CH01370017	Sb018-1B-12H Silver Brushed 3 X 2440	Silver Brushed
CH01370018	Sb018-2B-12H Gold Brushed 3 X 2440	Gold Brushed
CH01370019	Sb018-3B-12H Rose Gold Brushed 3 X 2440	Rose Gold Brushed
CH01370056	SBP018-4B-12H Brushed Black 3 X 12 X 2500	Brushed Black

description	Standard
Length	2440 - 2500 mm
Width	3 mm
Thickness	0.8 mm
Depth	12 mm
Material	Stainless Steel
Type	304
Fire resistance:	M0 (UNE 23-727-90)
Appearance and color	EN 12373-1
Corrosion resistance	High corrosion resistance
Operability	High in various places
Rust resistance	Stainless
Magnet	Not magnet attraction
Heat and cold resistance	High

Installation :

It's widely applied to transition of tile, stone, wooden laminates, door boards and wall decorative strips.

- 1.Cut profile to the desired length and apply the adhesive on the support where the profile will be laid.
- 2.Remove carefully any remains of oil, fat and dirt from the surface where the profile will be laid.
- 3.Apply the adhesive to the surface of the substrate.
- 4.Insert the profile into the gap between the tile (wood board, door or stone, etc.).
- 5.Remove immediately all the remains of grout from the surface of the profile and tile (wood board, door or stone, etc.).

Cleaning and maintenance :

We recommend: Wash the surface with soapy water or a mild detergent. Always rinse with clean water. Dry with a soft cloth.

Checked By QUALITY DEPARTMENT

occupational health and safety
GB/T45001-2020/ISO 45001:2018



Quality Management System ISO 9001

