

TECHNICAL DATA

Ref : G463R - G413R - G413R - G463R

DRY PRESSED CERAMIC TILES WITH WATER ABSORPTION LOWER THAN 0.5%
 Rectified porcelain

Product Name: **GRUPO Bla**

Item number	Product name	Critical Angle of Sliding
CH014100118	ROMA STONE SOMKE SATIN 60X120 Spanish porcelain	R9
CH014100119	ROMA STONE SOMKE SATIN 100X100 Spanish porcelain	R9
CH014100120	ROMA STONE GRAPHITE SATIN 100X100 Spanish porcelain	R9
CH018900026	ROMA STONE GRAPHITE SATIN 60X120 Spanish porcelain	R9

Standard	Features	Required Value	Value
EN-ISO 10545 / 3	Water absorption	0, % ≤ E ≤ 3%	E < 0,5%
EN-ISO 10545 / 4	Breaking strength	≥ 1100 N	≥ 1300 N
EN-ISO 10545 / 4	Bending strength	≥ 23 N/mm ²	≥ 35 N/mm ²
UNE EN ISO 10545-12	Durability; Freeze - thaw cycle	Required	Complies with
EN-ISO 10545 / 11	Crazing resistance	Required	Complies with
ISO 10545-7	Resistance to surface abrasion	1 - 5	Consult according to model
	Aesthetic classification and shade variations:		V.2
EN-ISO 10545 / 14	Stain resistance	Min. class 3	Class 5
UNE EN ISO 10545-13	Resistance to High concentration acids	Min. LB	Complies with
UNE EN ISO 10545-13	Household chemicals and swimming pool salts	Min. B	Complies with
UNE EN ISO 10545-13	Low concentration of alkalis	Min. LB	Complies with