

TECHNICAL DATA

built-in skirting profile , with LED lighting system.

Reference number : Am704

Size: 12x70x2500 mm

Thickness: ± 1 mm

(There may be slight size differences)

CH01370035

Am704 Aluminum Silver Matt 22 X 42 X 2500

Silver Matt

Description	Standard
Length	2500 mm
Width	12 mm
Height	70 mm
Thickness	± 1 mm
Material	Aluminum
Fire resistance	UNE 23-727-90
Appearance and color	EN 12373-1
Lightfastness	Excellent

Installation :

It's widely applied to transition of tile, stone, wooden laminates, door boards and wall decorative strips.

- 1.Cut profile to the desired length and apply the adhesive on the support where the profile will be laid.
- 2.Remove carefully any remains of oil, fat and dirt from the surface where the profile will be laid.
- 3.Apply the adhesive to the surface of the substrate.
- 4.Press the anchoring flange of profile into the adhesive.

Cleaning and maintenance :

The product must be cleaned periodically with a soft mop. If you use a neutral liquid cleaner, you must rinse the profile with cold water and dry it to remove the humidity excess. The persistent dirtiness can be removed by using cleaning approved agents lightly abrasive or a grid covered with polished powder neutral. Steel wool, abrasive cleaners, souring products as well as strong acids (hydrochloric and perchloric), strong bases (caustic soda or ammonia) or carbonated solutions are not recommended. Citric acid is neither recommended because dissolves the protective layer of the surface of aluminium. Waxes, petrolatum, lanolin or similar substances are not appropriate. Solvents containing haloalkanes (hydrofluoroether and chlorinated solvents) and curing accelerators containing chlorides should not be used (use special accelerators free of chlorides)

Checked By QUALITY DEPARTAMENT

occupational health and safety

GB/T45001-2020/ISO 45001:2018



Quality Management System ISO 9001

