

TECHNICAL DATA

Ref : G462R – G412R - G333R

DRY PRESSED PORCELAIN TILES WITH WATER ABSORPTION LOWER THAN 0.5%
Rectified porcelain

Product Name: **GRUPO Bla**

CH014100102	بورسلان إسباني 100X100 AVIGNON BONE MT
CH014100109	بورسلان إسباني 60X60 AVIGNON BONE MT RECT
CH01410096	بورسلان إسباني 60X120 AVIGNON BONE MT RECT

Standard	Features	Required Value	Value
EN-ISO 10545 / 3	Water absorption	0, % ≤ E ≤ 3%	E < 0,5%
EN-ISO 10545 / 4	Breaking strength	≥ 1100 N	≥ 1300 N
EN-ISO 10545 / 4	Bending strength	≥ 23 N/mm ²	≥ 35 N/mm ²
UNE EN ISO 10545-12	Durability; Freeze - thaw cycle	Required	Complies with
EN-ISO 10545 / 11	Crazing resistance	Required	Complies with
ISO 10545-7	Resistance to surface abrasion	1 - 5	Consult according to model
Aesthetic classification and shade variations:			V.2
EN-ISO 10545 / 14	Stain resistance	Min. class 3	Complies with
UNE EN ISO 10545-13	Resistance to High concentration acids	Min. LB	Complies with
UNE EN ISO 10545-13	Household chemicals and swimming pool salts	Min. B	Complies with
UNE EN ISO 10545-13	Low concentration of alkalis	Min. LB	Complies with