

Make your boundaries Stand Out

LED RECESSED WALL LUMINAIRE SERIES

PRODUCT INFORMATION

- Surface mounted, exterior-rated and compact sized architectural LED edge lighting luminaire that is designed for façade and outdoor decorative lighting applications.
- Ideal for edges lighting on windows and doors inner frames, building façades, landmarks and monuments.
- ILLUS LED RECESSED WALL Luminaire gives the customer the flexibility to choose between 5 models based on their specific need.

BENEFITS

- Unique optical distribution to highlight the inner frames or outer edges of windows, balconies or doors.
- Compact size.
- Light weight.
- Equipped with surge protective device.

FEATURES

- High CRI>80.
- Operating Voltage AC220-240V.
- Non-Dimmable.
- Good Impact Rating.



AREAS OF APPLICATION







Industrial


Garden Commercial

I TECHNICAL OPERATING & ELECTRICAL DATA


Input Voltage & Frequency	AC220-240V, 50/60Hz
Rated CRI	80
Color Temperature	3000K
IK Rating	IK10
IP Rating	IP65
IEC Classification	Class I
Lifespan	30000H
Switching Cycle	15000x on/off
Warranty Period	36 Months

SPECIFICATIONS


Code No.	Model No.	Body Color	Body Material	Power	Lumen	Surge Protection	TA	Beam Angle
541071	ILS6WLWW14	Dark Grey	Aluminum	7W	147lm	1kV	25°C	75°
541072	ILS6WLWW15	White	Aluminum	7W	147lm	1kV	25°C	75°
541073	ILS3WLWW05	Dark Grey	Aluminum	3W	68lm	0.5kV	25°C	74°
541074	ILS3WLWW06	White	Aluminum	3W	68lm	0.5kV	25°C	74°
541089	ILS12WLWW06	Dark Grey	Aluminum	13W	279lm	2kV	-20°C~45°C	57°







541073, 541074



541089



APPLICATION IMAGE



LED RECESSED WALL LUMINAIRE SERIES

BEYOND LIGHT..
TO THE LAST DETAILS!

