

**□ PRO** 

# Simple & Flexible Solution

## LED RECESSED LINEAR LUMINAIRE (CORNER)

#### PRODUCT INFORMATION

- Modern looking, neat luminaire offering comfortable, good quality lighting and can also work as a design element.
- Ideal lighting in the non-working areas of professional spaces such as offices, Educational institutes, and also the welcoming areas and entrances of retail spaces.
- ILLUS LED RECESSED LINEAR Luminaire (CORNER) gives the customer the flexibility to choose between 6 models with lumen package from 390lm to 700lm.

#### **BENEFITS**

- Uniform light.
- Multiple application use.
- Easy to install and maintain.

#### **FEATURES**

- High CRI>85.
- Efficacy up to 91lm/w.
- Long lifespan 50000H.
- Wide operating voltage AC220-240V.
- Non-Dimmable.



## **AREAS OF APPLICATION**





Hospitality

Shopping Center





Commercial

Educational Center




## I TECHNICAL OPERATING & ELECTRICAL DATA


| Body Color          | White               |  |  |
|---------------------|---------------------|--|--|
| Body Material       | Aluminum            |  |  |
| Rated CRI           | 85                  |  |  |
| IP Rating           | IP20                |  |  |
| Voltage & Frequency | AC220-240V, 50/60Hz |  |  |
| Dimming             | Non-Dimmable        |  |  |
| Beam Angle          | 110°                |  |  |
| Ambient Temperature | -20°C~45°C          |  |  |
| IEC Classification  | Class I             |  |  |
| Lifespan            | 50000H              |  |  |
| Switching Cycle     | 100000x on/off      |  |  |
| Warranty Period     | 60 Months           |  |  |
|                     |                     |  |  |

## **SPECIFICATIONS**

| Code No. | Model No.         | Power | Lumen | Efficacy  | CCT   | Culting Size  |
|----------|-------------------|-------|-------|-----------|-------|---------------|
| 611511   | ILS8.8RLLC840NW01 | 8W    | 690lm | 86.25lm/W | 4000K | L190*L190*H75 |
| 611311   | ILS8.8RLLC830WW01 | 8W    | 680lm | 85.00lm/W | 3000K | L190*L190*H75 |
| 611312   | ILS8.8RLLC857DL01 | 8W    | 700lm | 87.50lm/W | 5700K | L190*L190*H75 |
| 611513   | ILS5.4RLLC840NW01 | 4.5W  | 400lm | 88.89lm/W | 4000K | L190*L190*H55 |
| 611315   | ILS5.4RLLC830WW01 | 4.5W  | 390lm | 86.67lm/W | 3000K | L190*L190*H55 |
| 611316   | ILS5.4RLLC857DL01 | 4.5W  | 410lm | 91.11lm/W | 5700K | L190*L190*H55 |

## **DIMENSIONS**





611513 - 611315 - 611316 611511 - 611312



LED RECESSED LINEAR LUMINAIRE (CORNER) BEYOND LIGHT..
TO THE LAST DETAILS!

