



LED PRO

LED BOLLARD LUMINAIRE SERIES

PRODUCT INFORMATION

- Suitable for a series of lighting applications such outdoor offices, commercial outdoor, gardens and general lighting area.
- Available in a wide variety of lumen packs and color temperature.
- ILLUS LED BOLLARD Luminaire gives the customer the flexibility to choose between 5 models based on their specific need with lumen package from 713lm to 913lm.

BENEFITS

- Compact design for better integration with the building.
- Comfortable light with high efficiency.
- Reliable performance for outdoor applications.
- Equipped with surge protective function.

FEATURES

- High CRI>85.
- Long life span 30,000H.
- Operating voltage AC220-240V.
- Non-Dimmable.
- Good Impact Rating.



**BEYOND LIGHT..
TO THE LAST DETAILS!**

AREAS OF APPLICATION



Workplace



Shopping Center



Commercial



Educational center




TECHNICAL OPERATING & ELECTRICAL DATA

Voltage & Frequency	AC220-240V, 50/60Hz
CCT	3000K
Dimming	Non-Dimmable
Ambient Temperature	25°C
IEC Classification	Class I
IP Rating	IP65
IK Rating	IK10
Lifespan	30000H
Switching Cycle	15000x on/off
Warranty Period	36 Months

SPECIFICATIONS


Code No.	Model No.	Body Color	Material	Power	Lumen	Efficacy	CRI	Beam Angle	Surge Protection
541148	ILS13SMOBDL01	Dark Grey	Aluminum	13W	913lm	70.23lm/w	80	342°	2kV
541149	ILS13SMOBDL02	Dark Grey	Aluminum	13W	913lm	70.23lm/w	80	342°	2kV
541150	ILS13SMOBDL03	White	Aluminum	13W	913lm	70.23lm/w	80	342°	2kV
541153	ILS13SMOBDL04	Dark Grey	Aluminum	13W	713lm	54.85lm/w	80	157°	2kV
541154	ILS13SMOBDL05	Dark Grey	Aluminum	13W	713lm	54.85lm/w	80	157°	2kV

DIMENSIONS



541148 - 541149 - 541150

I DIMENSIONS



541153 - 541154



This image is for display purpose only, the image may differ from the actual product, as the product is subject to modification provided without prior notice.

LED BOLLARD LUMINAIRE SERIES

**BEYOND LIGHT..
TO THE LAST DETAILS!**

